

ELECTRONIC TOLL COLLECTION TAG HOLDER FOR A MOTORCYCLE

Background

With electronic toll collection (ETC) systems, motorists can pay for bridge and highway tolls without the traditional cash exchange. A motorist sets up a debit account from which toll payment is deducted. The debit account is funded either by check at the discretion of the motorist, or automatically by credit card each time the debit account reaches a minimum threshold. Once the account is set up, the motorist receives an electronic tag that corresponds to his payment information. The toll booths of the ETC system have a receiving antenna that detects the tag and sends its information (payer identification, account information and method of payment) to a central billing system to deduct the toll amount from the motorist's corresponding account. For the antenna to read the tag, it must be within a certain reading zone (usually the middle of the toll lane within a certain height range). ETC systems are more convenient than traditional cash based systems providing faster service and shorter lines at toll booths. It is expected that eventually, ETC systems will replace cash-based toll collection entirely.

Motorcycle operators have problems using ETC systems for lack of a suitable place to mount the tag, and therefore, cannot enjoy the benefits of an ETC system. In automobiles, the tags are usually fixed to the inside of the windshield. Such a mounting arrangement on a motorcycle, however, is not practical. At highway speeds, wind resistance creates violent turbulence that rips the tag off the windshield. Mounting surfaces are not available as most of the exposed surfaces on motorcycles are functional components (i.e., gas tank, oil reservoir, suspension components) that cannot be drilled or otherwise altered to hold or secure the ETC tag.

Typically, a motorcycle driver has to come to a complete stop at an ETC toll booth, remove the tag, usually from a pocket or bag, and search for the proper reading zone before they can continue passed the toll. This usually takes longer than the traditional cash exchange. As a result, ETC systems are an inconvenience to motorcycle operators and there is a need for an ETC tag holder that can attach to a motorcycle without interfering with the operation of the motorcycle and the

reading of the ETC tag.

Summary of the Invention

A ETC tag holder according to an embodiment of the present invention comprises an open-top, hollow body of sufficient size to accommodate an ETC tag therein. When an ETC tag is inserted into the hollow body, the tag projects upwardly, out of the body. The hollow body has a bottom surface for receiving the bottom of an inserted ETC tag. Means for securing the ETC tag as well with means for adjustably mounting the hollow body on a motorcycle.

Brief Description of the Drawings

Figure 1 shows a securing case for an ETC tag holder according to an embodiment of the present invention.

Figure 2 shows a side view of the case in Fig. 1.

Figure 3 shows the case of Fig. 1 with an ETC tag inserted therein and secured by an elastic band.

Figure 4 depicts an exemplary means for mounting the case of Fig. 1-3 according to an embodiment of the present invention.

Figure 5 shows the case of Fig. 1 secured to the means for mounting of Fig. 4.

Figure 6 shows an alternative embodiment of the means for mounting in Fig. 4.

Figure 7 depicts the means for mounting of Fig. 6 secured to the case of Fig. 1-3.

Figure 8 shows the case of Fig. 3 mounted on the handlebars of a motorcycle..

Figure 9 shows an alternative mounting configuration for the securing case of Fig. 8.

Figure 10 shows another alternative mounting configuration for the case of Fig. 8.

Figure 11 shows a securing case for an ETC tag holder according to an alternative embodiment of the present invention with a finger slot.

Figure 12 shows a securing case for an ETC tag holder according to another alternative embodiment of the present invention with more than one finger slot.

Figure 13 shows a securing case for an ETC tag according to an embodiment of the present invention, from the back, with a finger slot provided in the back panel.

Figure 14(a)-14(b) show alternative embodiments of a securing case for the ETC tag holder of the present invention where mounting apertures are provided on the side and top of the back panel.

Figures 15(a)-15(b) show an ETC tag securing case according to an embodiment of the present invention with a lid.

Figures 16(a)-16(b) depict a side view of the case in 15(a) - 15(b).

Figures 17(a) - 17(b) show an alternative embodiment of the case in Fig. 15(a) - 15(b).

Figure 18 shows an ETC tag securing case according to another alternative embodiment of the present invention with a lid.

Figure 19 depicts a back view of an ETC tag securing case with an alternative embodiment of a document holder with a finger slot.

Detailed Description

Figure 1 shows a securing case for an ETC tag holder in accordance with a preferred embodiment of the present invention. A securing case generally indicated by reference numeral 100, preferably made of plastic, comprises a back panel 12 with a bottom surface 17 extending outwardly from the panel 12 at a substantially right angle. A receptacle wall 14 extends upwardly from the outer edge of the bottom surface 17 along its outer edge length so that the back edges of the receptacle wall 14 connect to the front of the panel 12 to define an open-top, hollow receptacle 200 for receiving an ETC tag (not shown). Tag securing holes 16 in the panel 12, that extend from front to back, may be provided for receiving an elastic band (not shown) that wraps around an inserted tag, securing it in the receptacle 14. Preferably, the tag securing holes are placed above the receptacle wall 14 and at the sides of the panel 12. A portion of the panel's 12 lower end extends below the bottom surface where a plurality of mounting holes 18 are disposed along its width. The number of holes provided is a design choice and are preferably spaced evenly apart to implement a number of mounting configurations, thereby accommodating a variety of handlebar shapes, sizes and rake angles (the angles at which a bar bends in relation to other portions of the bar).

The case 100 is preferably made of plastic to avoid interference between the receiving antenna and the tag. The conductive properties of metals have been found to interfere with the signal produced by ETC tags, preventing the receiving antenna from reading the tag properly. The pieces of the case, namely, the back panel 12, the receptacle wall 14 and the bottom surface 17, may be attached to each other by an adhesive, such as glue or an epoxy resin. In addition, a document holder in the form of a downward, slot-shaped cavity 11 may be provided in the panel 12 to hold and secure documents and papers such as registration cards, insurance cards, licenses or any other documentation that may be necessary to operate a motorcycle.

Figure 2 shows a side view of the securing case 100 of Fig. 1 with similar components bearing similar reference numerals. As previously described with reference to Fig. 1, in Fig. 2 a back

[illegible][illegible][illegible]

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

used in conjunction with any number and combination of the mounting holes 18. An ETC tag 20 is inserted into the hollow receptacle of the case 100 and, in this example, secured to the panel 12 by tag securing means 13 which may be double-sided adhesive tape or velcro tape as an alternative to the elastic band 32 shown in Fig. 3.

Figure 6 shows an alternative embodiment of the means for mounting, generally indicated by reference numeral 60. Two halves 62 and 64 are joined over a cylindrical motorcycle member (not shown) and secured by a first bolting element (not shown) passing through a threaded hole 62.2 and 64.2 in the upper end of each half and a second bolting element (not shown) passing through a threaded hole 64.3 and 62.3 in the lower end of each half. The interior of each half 62 and 64 defines the clamping portion 67. The right half 64 has an engaging portion 65 for receiving a third bolting element 22 that passes through the mounting holes of a case to secure the case to the means 60, as depicted in Fig. 7.

Referring now to Fig. 7, a case 100 holds a tag 20 as previously described with similar components bearing similar reference numerals. The clamping portion 67 clamps around a motorcycle handlebar, for example, when the two halves 62 and 64 are securedly joined by first bolting element 60.1 and second bolting element 60.2. The third bolting element 22 secures the case 100 to the mounting means 60.

Referring to Figure 8, the securing case 100 is shown attached to a motorcycle 30, again similar components bearing similar reference numerals as in previous figures. The means for mounting 24 are clamped onto the handlebar 32. The bottom of the back panel 12 is secured to the clamp 24 by a bolting element 22 passing through a mounting hole in the panel and the engaging portion of the mounting means as depicted in Fig. 5. The tag 20 is placed in the hollow receptacle of the securing case 100 and may be secured by the double-sided tapes of Fig. 5 or the elastic band shown in Fig. 3.

The securing case may be mounted by any number of mounting means up to the number of

mounting holes provided in the panel. For example, if five mounting holes are available, up to five different mounting means may be used, depending on the handlebar space available. In addition, any combination of mounting holes may be used. Figure 9 shows a mounting configuration for the securing case 100 with an ETC tag 20 and two sets of mounting means at opposite ends of the back panel 12. The first set 24.10 is secured to the back panel 12 by bolting element 22.10 passing through the mounting hole on the far left of the back panel 12 and engaging the engaging portion of the mounting means 24.10, as previously discussed. The second set 24.20 is secured to the panel 12 by a second bolting element 22.20. Figure 10 shows a mounting configuration with one set of mounting means 24 and one bolting element 22 secured to the back panel 12 through a mounting hole that is off-center. This configuration works where there is insufficient horizontal space on a handlebar to accommodate more than one mounting means.

Figure 11 shows a securing case according to an alternative embodiment of the present invention generally indicated by reference numeral 70 where the receptacle wall 74 has a finger slot 72 extending into the hollow receptacle 200 so that a finger can get into the hollow receptacle 200 to easily remove an ETC tag (not shown) contained therein. The receptacle wall should extend virtually all the way to the top of the panel 12 to ensure that a received tag is secure. An elastic band (not shown) may be used for added stability in securing the tag by wrapping the band around the case 70 in a vertical direction.

Figure 12 shows another alternative embodiment of the securing case generally indicated by reference numeral 80 where one finger slot 82.2 is provided on the left of the receptacle wall 84 and another slot 82.1 on the right of the receptacle wall 84. With this embodiment, fingers can grasp an ETC tag (not shown) by its sides to be upwardly removed by placing one finger through the left finger slot 82.2, and another finger through the right finger slot 82.1.

Figure 13 depicts an ETC tag holder 1010 from the back. In this particular embodiment, a finger slot 1170 is provided in the back panel 12 extending into the document holder cavity 11. With

the slot 1170, it is easier to remove any documents such as registration or insurance cards, from the cavity 11 that may be contained therein.

Figures 14(a) and 14(b) show other embodiments of the invention where the mounting holes 18 are disposed along different sides of the panel 12. In Fig. 14(a), a portion of the left side of the panel 12 extends beyond the receptacle wall 14. The mounting holes 18 are provided in the portion that extends beyond the wall 14 on the left side of the panel 12. The receptacle wall 14 and bottom surface 17 are positioned so that the hollow receptacle is open on top to receive an ETC tag. In Fig. 14(b), the bottom surface 17 and receptacle wall 14 are moved toward the lower end of the panel 12 and the mounting holes 18 are disposed along the top of the panel 12.

Figure 15(a) shows yet another alternative embodiment of the present invention with a securing lid 150. The securing case 100 of the previous embodiments is attached to a lid 150 by hinges 152 at the top of the back panel 12. Means for fastening the lid 150, such as a male clasp 154.1 integrated into the lid 150 for a female clasp 154.2 on the receptacle wall 14, may be provided. An ETC tag (not shown) is placed in the hollow receptacle 200 and secured by closing the lid 150 and securing the male clasp 154.1 on the female clasp 154.2. Figure 15(b) shows the case of Fig 15(a) in a closed configuration with similar elements bearing similar reference numerals.

Figure 16(a) and 16(b) show a side view of the case in Fig 15(a) and 15(b) with similar elements bearing similar reference numerals.

Figure 17(a) shows an alternative embodiment for the lid of Fig 15(a) with similar elements bearing similar reference numerals. As previously described, a securing case 100 comprises the back panel 12, receptacle wall 14, and bottom surface 17 interconnected to form a hollow receptacle 200 for removably receiving an ETC tag. A lid 170, shaped to enclose substantially all of the hollow receptacle portion, is attached to the top of the panel 12 by hinges 172. Means for fastening the lid 170, such as a male clasp 174.1 is provided in the lid 170 to engage a female clasp 174.2 on the receptacle wall 14, to hold the lid 170 in a closed position against the

receptacle wall 14 as shown in Fig. 17(b). In the closed position of Fig. 17(b), the case 100 is a completely enclosed box.

Figure 18 shows another alternative embodiment of the lid in previous Figures 15(a) - 17(b). In this particular embodiment, the receptacle wall 184 extends virtually all the way to the top of the back panel 12. A lid 180 is substantially flat and shaped to fit onto the top of the receptacle wall 184 when closed. The lid 180 is fixed to the case 70 at the top of the panel 12 by pins 180.1. Although not shown, the lid may be secured to the receptacle wall 74 by a clasp, velcro, or any other suitable fastening means.

Figure 19 shows another alternative embodiment of the present invention where the back panel 12 has a left sidewall 194, a right sidewall 194.1 and a second bottom surface 197 attached to its backside. A second panel 190 is attached to the sidewalls 194.1 and 194.2 and the bottom surface 197 to form a receptacle for a document holder. The second panel 190 preferably has a finger slot for easy removal of contents. This embodiment may be used as an alternative to the cavity slot document holder in the back panel described in previous embodiments. It should be noted that when this embodiment of the document holder is combined with any other embodiment including a lid, the lid may be sized and positioned to cover the document holder as well as the hollow receptacle chamber.

All ETC tag holders within the scope of this disclosure may include any combination of the finger slots, document holder, tag securing holes, drainage holes, lids, and different positions of the mounting holes disclosed herein. For example, an ETC tag holder according to one embodiment may have finger slots in the receptacle wall for the ETC tag and finger slots in the back panel for the document cavity, with mounting holes on the side. A tag holder according to an alternative embodiment may have a finger slot for the document holder only with mounting holes on top and no tag securing apertures. In yet another embodiment, the document holder, drainage holes and tag securing holes may all be left out of the design.

In the preceding specification, the invention has been described with reference to specific exemplary embodiments and examples thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the claims that follow. The specification and drawings are accordingly to be regarded in an illustrative manner rather than a restrictive sense.